





Feature:

- 8 10/100Mbps Auto-Negotiation RJ45 ports, Supports Auto MDI / MDIX
- Green Ethernet technology saves the power up to 60%
- IEEE 802.3x flow control provides reliable data transfer
- Metal case, desktop design
- Plug and play, no configuration required

Features

Acorid 8-Port 10/100Mbps desktop switch provides an easy way to expand your wired network. All 5 ports support auto-MDI/MDIX, eliminating the need to worry about the type of cable to use. Featuring full duplex mode. With innovative energy-efficient technology, the LS5305 can save up to 60% of power consumption, making it an ecofriendly solution for your home or office network.

High Performance

Acorid Fast Ethernet Switch provides 8 10/100Mbps Auto-Negotiation RJ45 ports. All ports support Auto MDI/MDIX function, eliminating the need for crossover cables or Uplink ports..Featuring non-blocking switching architecture,LS5305 forwards and filters packets at full wire-speed for maximum throughput. With 10K Jumbo frame, the performance of large files transfers is improved significantly. And IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode alleviate the traffic congestion and make it work reliably.

Easy to Use

The auto features of this ethernet switch make installation plug and play and hassle-free. No configuring is required. Auto MDI/MDIX eliminates the need for crossover cables. Auto-negotiation on each port senses the link speed of a network device (10, 100 Mbps) and intelligently adjusts for compatibility and optimal performance.

Technical Specification:

HARDWARE FEATURES		
Interface	8 10/100Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX	
External Power Supply	100-240VAC, 50/60Hz	
Dimensions (W X D X H)	217 x 105x 28mm	
Fan Quantity	Fanless	

SOFTWARE FEATURES

Transfer Method	Store and Forward
Advanced Functions	Green Technology, saving power up to 60% 802.3X Flow Control, Back Pressure Auto-Uplink Every Port

OTHERS

Certification	FCC, CE, RoHs
Package Contents	8-Port 10/100Mbps Desktop Switch Power Adapter User Guide
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux
Environment	Operating Temperature: 0° ~40 $^{\circ}$ (32 $^{\circ}$ ~104 $^{\circ}$); Storage Temperature: -40° ~70 $^{\circ}$ (-40 $^{\circ}$ F~158 $^{\circ}$); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing

Ordering information:

S3009F 8 ports 10/100Mbps fast Fiber Ethernet Switch