

Enterprise Gateway/ Controller

Pulsar Uniti Smart Gateway 128

SERIES

Indoor

Models

Pulsar Uniti Smart Gateway 128



MAIN FEATURES

- Multi-WAN and multi-WAN port load balancing
- 2 Support cloud access
- 3 Manange 128PCS AP
- 4 Intelligent flow control
- **5** Remote management
- 6 Enterprise level gigabit routing gateway
- 7 High performance architecture provides a better network experience
- 8 High reliability. Safe and stable
- Easy operation and maintenance
- 10 Cloud Platform
- Business integration to meet diversified needs
- 12 Meet multi scenario applications
- 13 Support multi operator access





Pulsar Uniti Smart Gateway 128

Model	Pulsar Uniti Smart Gateway 128
Hardware Specifications	
DDR	512M
Flash	16M
Heat Dissipation	Natural heat dissipation
Interface	4*Gigabit LAN (can be configured to multi WAN)
	1*Gigabit WAN
	1*Console
	1*USB3.0
Power	DC: 12V
Size	232.5 *152.5 *44.5mm
Working Temperature	-20°C∼55°C
Storage Temperature	-40°C ~ 70°C
Working Humidity	5%∼97%RH (No condensation)

The maximum number of managed users is 128 users
The AP management number is 128 units
Centralized and remote management, to configure the wireless AP
Total number of users, current links, online devices, and offline devices
On-access real-time rate, running time, user management, device management
Equipment information, equipment description, Intranet information, extranet information
List of equipment
Template Settings
Device upgrade
service configuration
IPTV set up
Automatic roaming
User list
User speed limit
IP filter
MAC filter
Website filtering
port mapped
DMZ set up
Connection mode: static address, dynamic acquisition (DHCP), broadband dial (PPPOE), bypass mode
DHCP server: either built-in DHCP server or external DHCP server
Cloud platform server
Backup Configuration Information
Restore configuration information
factory data reset
Restart immediately
firmware upgrade
Time management includes the system display time and time synchronization
system log