

DHI-HY-C133 Conventional Smoke Detector



- Four-wire, polarity-free realizes convenient wiring
- BLC algorithm automatically adjusts alarm threshold based on the smoke in the chamber, extending cleaning cycle and providing easier maintenance
- Non-loosening screws on base terminal for easy installation
- · Contacts material is highly acid-resistant and rust-resistant

System Overview

DHI-HY-C133 Conventional Smoke Detector is a mated product of the Conventional Fire Alarm Control Panel. Integrated with four-wire and polarity-free technology, this detector analyzes ambient smoke concentration through a dual photoelectric smoke sensing chamber.

Technical Specification

•	•	
Working Voltage	DC 9V-28V	
Current	Standby current: ≤ 350μA Alarm current: ≤ 100mA	
Alarm Mode	Visual and audible alarm	
Coverage Area	$H \le 4 m (13.12 ft): 150 m^2$ 4 m (13.12 ft) $\le H \le 12 m (39.37 ft): 80 m^2$	
Operating Temperature	-10°C to +55°C (+14°F to +131°F)	
Operating Humidity	\leq 95% RH (no condensation)	
Dimensions (with base)	104 mm × 103.6 mm × 46 mm (4.09" × 4.08"× 1.81")	
Weight (with base)	122 g (0.27 lb)	
Installation	Ceiling Mount	

Functions

Built-in buzzer

With a built-in buzzer, the detector sends out audible alarm when a fire occurs.

Dual photoelectric smoke sensing chamber

The smart algorithm of automatic compensation against dust concentration helps adjust alarm threshold, prolong cleaning cycle of chamber, and offering a convenient maintenance.

Non-addressable

Without encoding, easy debugging and operating.

Scene

It is suitable for apartments, hotels, teaching buildings, office buildings, banks, libraries, warehouses, computer rooms, communication machine rooms, archives, and other industrial and civil buildings.

Installation



Dimensions (mm/inch)





Ordering Information		
Туре	Part Number	Description
Conventional Smoke Detector	DHI-HY-C133	Conventional Smoke Detector

 $\mathbb O$ 2023 Dahua. All rights reserved. Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail. Rev 001.001