

WiFi 6 Outdoor Access Point

Pulsar Uniti X6 Outdoor LR

SERIES

Outdoor Wall-Mount

Models

Pulsar Uniti X6 Outdoor LR

**MAIN FEATURES**

- ① High-speed 11ax outdoor dual-band AP
- ② Supports Repeater mode and AP mode
- ③ Dual-Band wireless transmission
- ④ POE power supply
- ⑤ Remote management
- ⑥ Automatic RF Tuning
- ⑦ Seamless Roaming
- ⑧ AC management
- ⑨ Hardware Watchdog
- ⑩ Cloud Platform
- ⑪ Cable Ports Hidden Design
- ⑫ Surge protection
- ⑬ Full Gigabit ports faster transmission
- ⑭ Plastic IP67 dustproof/waterproof design
- ⑮ Built in 4 pieces antennas with an angle of 360°
- ⑯ Allow 128 terminals to simultaneously access the internet

www.pulsar.az

Pulsar Uniti X6 Outdoor LR

Model	Pulsar Uniti X6 Outdoor LR				
Hardware Specifications					
Flash	SPI NOR 16MB				
DDR3	256MB				
2.4G Frequency	2.4GHz ~ 2.484GHz				
2.4G WIFI protocol	802.11 b / g / n / ax				
5.8G Frequency	4.9GHz~5.9GHz				
5G WIFI protocol	802.11 a / n / ac / ax				
Antenna	Build in 4*5dBi dual band MIMO Antenna				
Wireless data rate	1800Mbps				
End Users	128+				
2.4G Power	802.11b	11M	22±2dBm	1M	22±2dBm
	802.11g	54M	19±2dBm	6M	21±2dBm
	802.11n HT20	MCS7	18±2dBm	MCS0	20±2dBm
	802.11n HT40	MCS7	18±2dBm	MCS0	20±2dBm
	802.11ax HT20	MCS11	16±2dBm	MCS0	20±2dBm
5G Power	802.11ax HT40	MCS11	16±2dBm	MCS0	20±2dBm
	802.11a	54M	19±2dBm	6M	21±2dBm
	802.11n HT20	MCS7	18±2dBm	MCS0	20±2dBm
	802.11n HT40	MCS7	18±2dBm	MCS0	20±2dBm
	802.11ac HT20	MCS7	17±2dBm	MCS0	20±2dBm
	802.11ac HT40	MCS7	17±2dBm	MCS0	20±2dBm
	802.11ac HT80	MCS9	17±2dBm	MCS0	19±2dBm
	802.11ax HT20	MCS11	16±2dBm	MCS0	20±2dBm
	802.11ax HT40	MCS11	16±2dBm	MCS0	20±2dBm
	802.11ax HT80	MCS11	16±2dBm	MCS0	19±2dBm
2.4G Receive Sensitivity	802.11ax HT160	MCS11	14±2dBm	MCS0	18±2dBm
	802.11b	11M	-87dBm	1M	-96dBm
	802.11g	54M	-75dBm	6M	-93dBm
	802.11n HT20	MCS7	-73dBm	MCS0	-92dBm
	802.11n HT40	MCS7	-70dBm	MCS0	-89dBm
5G Receive Sensitivity	802.11ax HT20	MCS11	-64dBm	MCS0	-92dBm
	802.11ax HT40	MCS11	-61dBm	MCS0	-89dBm
	802.11a	54M	-74dBm	6M	-92dBm
	802.11n HT20	MCS7	-73dBm	MCS0	-90dBm
	802.11n HT40	MCS7	-70dBm	MCS0	-87dBm
	802.11ac HT20	MCS7	-67dBm	MCS0	-91dBm
	802.11ac HT40	MCS7	-63dBm	MCS0	-88dBm
	802.11ac HT80	MCS9	-60dBm	MCS0	-84dBm
	802.11ax HT20	MCS11	-62dBm	MCS0	-91dBm
	802.11ax HT40	MCS11	-59dBm	MCS0	-89dBm
2.4G EVM	802.11ax HT80	MCS11	-56dBm	MCS0	-86dBm
	802.11ax HT160	MCS11	-53dBm	MCS0	-83dBm
5G EVM	802.11b:≤-10 dB ; 802.11g:≤-25 dB ; 802.11n:≤-28dB ; 802.11ax: ≤-35 dB				
ppm	802.11a:≤-25 dB ; 802.11n:≤-28 dB ; 802.11ac:≤-32 dB ; 802.11ax:≤-35 dB				
WAN	±20ppm				
LAN	1 * 10/100/1000Mbps RJ45 WAN port and PoE port, support 48V POE				
Reset	1 * 10/100/1000Mbps LAN port				
Indicator	1 * Reset button, press 10 seconds to revert to default setting				
Power	Sys and WiFi, WAN, LAN				
Max Power Consumption	48V (IEEE 802.3af/at)				
RF Power	≤ 15W				
	≤18dBm				
Size					
L*W*H	303mmX180mmX87mm				
Weight	0.55kg				
Working Environment					
Working Temperature:	-20℃~45℃				
Storage Temperature	-40℃~70℃				
Working Humidity	10%~90% No Condensation				
Storage Humidity	5%~95% No Condensation				