

Unmanaged Gigabit Poe Switch

Pulsar Uniti switch 4GP-65

SERIES

Unmanaged Switch

Models

Pulsar Uniti switch 4GP-65

**MAIN FEATURES**

- ① The POE detection chip adopts the 802.3af/at standard protocol
- ② The design life is 3 years
- ③ The high-frequency and low-resistance capacitors make the equipment performance more st
- ④ A single port supports the AT protocol and supports up to 30W
- ⑤ Port are automatically flipped
- ⑥ Plug-and-play simple networking
- ⑦ The metal body dissipates heat efficiently stable operation
- ⑧ Efficient data transfer
- ⑨ AC and cold start function
- ⑩ Gigabit up-link port and Gigabit PoE ports
- ⑪ Gigabit SFP fiber injector
- ⑫ Designed with desktop metal case
- ⑬ Easy to make the transition to Gigabit Ethernet.



www.pulsar.az

Pulsar Uniti switch 4GP-65

| Model | Uniti switch 4GP-65 |
|---|--|
| Hardware Specifications | |
| Network standard | IEEE802.3 10BASE-T Ethernet IEEE802.3u 100BASE-TX faster Ethernet IEEE802.3ab 1000BASE-T gigabit Ethernet ANSI/IEEE 802.3 NWay Auto-Negotiation IEEE802.3 af IEEE802.3at |
| Ports | 4 * 10/100/1000M auto Negotiation /auto MDI/MDIX PoE Ports 1 * 10/100/1000M auto Negotiation /auto MDI/MDIX up-link Port 1 * 1000M SFP Fiber Port |
| Cable requirement | 10BASE-T: UTP 3, 4, 5 cable (≤100 meters) 100BASE-TX: UTP 5 cable (≤100 meters) 1000BASE-TX: UTP 5 cable (≤100 meters) |
| IEEE802.3 af | Support/15.4W |
| IEEE802.3at | Support/30W |
| LED Indicator | PWR LINK for each port |
| Power Supply | AC 100 V~240 V 50/60 Hz |
| Power over Ethernet (PoE) Specifications | |
| POE | 65W, up to 30W for PoE port |
| PoE Standard | IEEE 802.3, 802.3u, 802.3x, 802.3af,802.3at |
| Overload Protection | 60W |
| Switch Performance | |
| Advanced Functions | Comply with IEEE 802.3at/af PDs Port Priority Function Support storage forwarding MAC Address Auto-Learning and Auto-Aging. IEEE802.3X Flow Control for Full-Duplex Mode and Backpressure for Half-Duplex Mode |
| Backplane Bandwidth | 12Gbps |
| MAC Address Table | 2K |
| Forwarding Rate | 10BASE-T:14800pps/port 100BASE-TX:148000pps/port 1000BASE-TX:1480000pps/port |
| Size | |
| L*W*H | 210mm*136mm*44.5mm |
| Working Environment | |
| Working Temperature: | 0°C~40°C |
| Storage Temperature | -40°C~70°C |
| Working Humidity | 10%~90% No Condensation |
| Storage Humidity | 5%~90% No Condensation |