

DS-K1T323MBWX-QRE1 Value Series Face Access Terminal



- 2.4-inch display screen, 2 Mega pixel wide-angle lens
- 1,000 face capacity, and 3000 card capacity
- Face recognition duration < 0.2 s/User
- Supports face, card, and QR code authentication
- Two-way audio with client software, indoor station, and main station.
- Supports AP mode. Supports mobile Web and PC Web for configuration
- Supports M1 card
- Supports powered by 12 VDC or PoE and supports powering for device and door lock.
- Supports WDR



Specification

System	
Operating system	Linux
Display	
Screen size	2.4-inch
Resolution	240 × 320
Туре	TFT
Operation method	Non touchable
Video	
Lens	×1
Video standard	PAL (Default) and NTSC
Network	
Bluetooth	Support
Wired network	10/100 Mbps self adaptive
Wi-Fi	Support
Interface	
PoE	IEEE802.3at, standard PoE
Network interface	1
Wiegand	1, supports Wiegand input, single direction
Lock control	1
Exit button	1
Door contact input	1
TAMPER	1
Capacity	
User capacity	1000
Card capacity	3000
Face capacity	1000
Event capacity	150000
Authentication	
Card type	M1 card,M1 card content,CPU card No.
Card reading frequency	13.56 MHz
Face recognition duration	< 0.33 s
Face recognition accuracy rate	> 99%
Face recognition distance	0.3 to 1.5 m
General	
Button	1 physical call button
Power supply	12 VDC, 1 A, standard PoE
Working temperature	-30 °C to 65 °C (-22 °F to 149 °F)
Working humidity	0 % to 90 % (no condensing)
Dimensions	157 mm × 52 mm × 26 mm (6.18" × 2.05" × 1.02")
Installation	Wall mounting
Protective level	IP65
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil), Turkish, French, Traditional Chinese




Weight	Net weight: 0.22 kg (0.49 lb) Rough weight: 0.6 kg (1.32 lb)	
Function		
QR code recognition	Support scan QR code via QR code module or camera	
Face anti-spoofing	Support	
Two-way audio	Support	
Audio prompt	Support	

Available Model

DS-K1T323MBWX-QRE1

Dimension



Accessory

Optional



See Far, Go Further



www.hikvision.com support@hikvision.com















