

**DS-PM1-RT-HWE**  
**868MHz Tri-X Wireless Receiver**

Tri-X wireless receiver, compatible with AX HYBRID PRO <sup>V1</sup> control panel, used to expand wireless capability of the control panel. HIKVISION Tri-X detectors can be added to AX HYBRID PRO <sup>V1</sup> panel via this wireless receiver.

- 868MHz wireless receiver
- Wireless transmission distance up to 1700m
- Supports 32 wireless detectors, 8 wireless indoor sounders and 4 wireless outdoor sounders

## ▪ Specification

Hardware features	
Bus	1 Speed-X bus
Electrical characteristics	
Power supply	9 to 28 VDC, 1A
Power consumption	Maximum current 100 mA@12 VDC; Quiescent current 40 mA@12 VDC
Wireless transmission	
RF frequency	868 MHz
Wireless security	Frequency hopping 128 AES encryption
Display	
LED Indicator	1. Green: power/find me 2. Orange: alarm/fault
General	
Dimension(WxHxD)	110 mm × 155 mm × 32 mm
Shell material	Plastic
Weight	225 g
Operation temperature	-10°C to 40°C
Operation humidity	10% to 90%
Device management	
Alarminput	Up to 32 wireless detectors(portable emergency button is not included)
Wireless sounder	Up to 8 wireless indoor sounder, 4 wireless outdoor sounder

## ▪ Available Model

DS-PM1-RT-HWE

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
[www.hikvision.com](http://www.hikvision.com)



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision\_Global



Hikvision  
Corporate Channel



hikvisionha