

ASL8112R-B ASL8112K-B ASL8112S-B

High-end Bluetooth smart lock



Technical Specification

Card

Card Type	Mifare 1
Card Features	Contactless, high security, all-in-one possible
Sensor Distance	< 20mm
Sensor Time	< 0.5s
Storage Capacity	50

Password

Keyboard Type	All-touch keyboard
Password Length	6-12 bits
Storage Capacity	50
Cin - a manint	

Fingerprint

Sensor	Capacitive
False Rejection Rate	≤0.1%
False Accept Rate	≤0.0001%
Fingerprint Capacity	50

Battery

Working Voltage	6V, "AA" battery (4pcs)
Battery Life	About 1 year (10 units/D)
Low Battery Warning	< DC4.5V
Emergency Power Supply	9V battery

Features

- 5-way opening: Easy4key App, Fingerprint, Mifare Card, password and mechanical key
- · Voice prompt: All settings can be finished by following voice prompt
- · Privacy password: xxx+password+xxx, preventing password to be seen by others
- · Passage Mode and Non-disturbance Mode optional
- ·Auto lock when come across a consecutive invalid passwords or cards
- · Low Voltage alarm(≤4.5V), doorbell
- · Huge storage: 50 Fingerprints, 50 cards, 50 passwords
- · Emergency power supply outside
- · Three colors optional
- · Zinc alloy material

Structure

Door Thickness	42-80mm (customizable)
Backset	60mm
Central Distance	68mm
Product Standard	GA374-2001(e-lock)
Material	Zinc alloy

General

Working Temperature	-30°C~+70°C
Relative Humidity	10%~93%
Salt spray test	≥200h
Lock case test	≥100000 times
Package size	410*225*155(mm)
Gross weight	6Kg
Restore Default	Support
Reset	Support
Ring	Support
Built-in Buzzer	Support
Built-in Loudspeaker	Support



Dimensions





